

Get a Quote

Overview

Cisco® Catalyst® 1000 Series Switches are fixed managed Gigabit Ethernet enterprise-class Layer 2 switches designed for small businesses and branch offices. These are simple, flexible and secure switches ideal for out-of-the-wiring-closet and critical Internet of Things (IoT) deployments. Cisco® Catalyst® 1000 operate on Cisco IOS® Software and support simple device management and network management via a Command-Line Interface (CLI) as well as an on-box web UI. These switches deliver enhanced network security, network reliability, and operational efficiency for small organizations.

Quick Specs

Table 1 shows the Quick Specs.

Product Code	C1000-48P-4G-L
Description	48x 10/100/1000 Ethernet PoE+ and 370W PoE budget ports, 4x 1G SFP uplinks
Gigabit Ethernet ports	48
Uplink interfaces	4 SFP
PoE+power budget	370W
Fanless	N
Dimensions (WxDxH in inches)	17.5 x 13.78 x 1.73
CPU	ARM v7 800 MHz
DRAM	512 MB
Flash memory	256 MB
Forwarding bandwidth	52 Gbps
Switching bandwidth	104 Gbps
Forwarding rate(64—byte L3 packets)	77.38 Mpps

Product Details

The Cisco Catalyst 1000 Series Switches provides these features:

- * 8, 16, 24, or 48 Gigabit Ethernet data or PoE+ ports with line-rate forwarding
- * 2 or 4 fixed 1 Gigabit Ethernet Small Form-Factor Pluggable (SFP)/RJ 45 Combo uplinks or 4 fixed 0 Gigabit Ethernet Enhanced SFP (SFP+) uplinks
- * Perpetual PoE+ support with a power budget of up to 740W
- * CLI and/or intuitive web UI manageability options
- * Network monitoring through sampled flow (sFlow)
- * Security with 802.1X support for connected devices, Switched Port Analyzer (SPAN), and Bridge Protocol Data Unit (BPDU) Guard
- * Compact fanless models available with a depth of less than 13 inches (33 cm)
- * Device management support with over-the-air access via Bluetooth, Simple Network Management Protocol (SNMP), RJ-45, or USB console access
- * Reliability with a higher Mean Time Between Failures (MTBF) and an enhanced limited lifetime warranty support(E-LLW)

Compare to Similar Items

Table 2 shows the comparison.

Product Code	C1000-48FP-4G-L	C1000-48P-4G-L	C1000-48T-4G-L	C1000-48FP-4X-L	C1000-48P-4X-L	C1000-48T-4X-L
--------------	---------------------------------	--------------------------------	--------------------------------	---------------------------------	--------------------------------	--------------------------------

Description	48x 10/100/1000 Ethernet PoE+ ports and 740W PoE budget, 4x 1G SFP uplinks	48x 10/100/1000 Ethernet PoE+ and 370W PoE budget ports, 4x 1G SFP uplinks	48x 10/100/1000 Ethernet ports, 4x 1G SFP uplinks	48x 10/100/1000 Ethernet PoE+ ports and 740W PoE budget, 4x 10G SFP+ uplinks	48x 10/100/1000 Ethernet PoE+ ports and 370W PoE budget, 4x 10G SFP+ uplinks	48x 10/100/1000 Ethernet ports, 4x 10G SFP+ uplinks
Gigabit Ethernet ports	48	48	48	48	48	48
Uplink interfaces	4 SFP	4 SFP	4 SFP	4 SFP+	4 SFP+	4 SFP+
PoE+power budget	740W	370W	\	740W	370W	\
Fanless	N	N	N	N	N	N
Dimensions (WxDxH in inches)	17.5 x 13.78 x 1.73	17.5 x 13.78 x 1.73	17.5 x 10.73 x 1.73	17.5 x 13.78 x 1.73	17.5 x 13.78 x 1.73	17.5 x 10.73 x 1.73
CPU	ARM v7 800 MHz	ARM v7 800 MHz	ARM v7 800 MHz	ARM v7 800 MHz	ARM v7 800 MHz	ARM v7 800 MHz
DRAM	512 MB	512 MB	512 MB	512 MB	512 MB	512 MB
Flash memory	256 MB	256 MB	256 MB	256 MB	256 MB	256 MB
Forwarding bandwidth	52 Gbps	52 Gbps	52 Gbps	88 Gbps	88 Gbps	88 Gbps
Switching bandwidth	104 Gbps	104 Gbps	104 Gbps	176 Gbps	176 Gbps	176 Gbps
Forwarding rate(64—byte L3 packets)	77.38 Mpps	77.38 Mpps	77.38 Mpps	77.38 Mpps	77.38 Mpps	77.38 Mpps

Get More Information

Do you have any question about the C1000-48P-4G-L?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

C1000-48P-4G-L Specification	
Description	48x 10/100/1000 Ethernet PoE+ and 370W PoE budget ports, 4x 1G SFP uplinks
Gigabit Ethernet ports	48
Uplink interfaces	4 SFP
PoE+power budget	370W
Fanless	N
Dimensions (WxDxH in inches)	17.5 x 13.78 x 1.73
Console ports	
RJ-45 Ethernet	1
USB mini-B	1
USB-A port for storage and Bluetooth console	1
Memory and processor	
CPU	ARM v7 800 MHz

DRAM	512 MB
Flash memory	256 MB
Performance	
Forwarding bandwidth	52 Gbps
Switching bandwidth	104 Gbps
Forwarding rate(64—byte L3 packets)	77.38 Mpps
Unicast MAC addresses	16000
IPv4 unicast direct routes	542
IPv4 unicast indirect routes	256
IPv6 unicast direct routes	414
IPv6 unicast indirect routes	128
IPv4 static routes	16
IPv6 static routes	16
IPv4 multicast routes and IGMP groups	1024
IPv6 multicast groups	1024
IPv4/MAC security ACEs	600
IPv6 security ACEs	600
Maximum active VLANs	256
VLAN IDs available	4094
Maximum STP instances	64
Maximum SPAN sessions	4
MTU-L3 packet	9198 bytes
Jumbo Ethernet frame	10,240 bytes
Dying Gasp	Yes
MTBF in hours (data)	1,452,667
MTBF in hours (PoE)	856,329
MTBF in hours (Full PoE)	856,329
Environmental	
Operating temperature Seal level	-5 to 50 deg C*
Up to 5,000ft (1500 m)	-5 to 45 deg C
Upto 10,000 (3000 m)	-5 to 40 deg C
Operating altitude	10,000 ft (3,000m)
Operating relative humidity	5% to 90% at 40C
Storage temperature	-13 to 158F (-25 to 70C)
Storage altitude	15,000 ft (4500m)

Storage relative humidit	5% to 95% at 65C
<p>*Note: 50C operation is supported for short term operation only; GLC-BX-D/U and CWDM optics cannot support 50C operation; Minimum ambient temperature for cold start is at 0C (32F)</p>	
Safety and compliance	
Safety	UL 60950-1 Second Edition, CAN/CSA-C22.2 No. 60950-1 Second Edition, EN 60950-1 Second Edition, IEC 60950-1 Second Edition, AS/NZS 60950-1, IEC 62368-1, UL 62368-1 GB 4943.1-2011
EMC: Emissions	47CFR Part 15 Class A, AS/NZS CISPR32 Class A, CISPR32 Class A, EN55032 Class A, ICES-003 Class A, VCCI-CISPR32 Class A, EN61000-3-2, EN61000-3-3, KN32 Class A, CNS13438 Class A
EMC: Immunity	EN55024 (including EN 61000-4-5), EN300386, KN35
Environmental	Reduction of Hazardous Substances (RoHS) including Directive 2011/65/EU
Telco	Common Language Equipment Identifier (CLEI) code
U.S. government certifications	TBD
Connectors and interfaces	
Ethernet interfaces	<ul style="list-style-type: none"> * 10BASE-T ports: RJ-45 connectors, 2-pair Category 3, 4, or 5 Unshielded Twisted Pair (UTP) cabling * 100BASE-TX ports: RJ-45 connectors, 2-pair Category 5 UTP cabling * 1000BASE-T ports: RJ-45 connectors, 4-pair Category 5 UTP cabling * 1000BASE-T SFP-based ports: RJ-45 connectors, 4-pair Category 5 UTP cabling
Indicator LEDs	<ul style="list-style-type: none"> * Per-port status: link integrity, disabled, activity * System status: system
Console cables	<ul style="list-style-type: none"> * CAB-CONSOLE-RJ45 Console cable 6 ft. with RJ-45 * CAB-CONSOLE-USB Console cable 6 ft. with USB Type A and mini-B connectors
Power	<ul style="list-style-type: none"> * Use the supplied AC power cord to connect the AC power connector to an AC power outlet * Models have external power supply

Want to Buy

Order Now

Get a Quote

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com